



XF-PTL13732-F

Optional camera mount
 1、 F
 2、 M42×1

Specification

Optical structure	Bi-Telecentric
Magnification	0.24
Object field of view	Φ133.3mm
Image field of view	Φ32mm
Working Distance	280mm±3%
Telecentricity	<0.04°(0.06°)
Depth of field	14.4mm
F#	F7.5
Resolution	20.7μm
MTF	>0.3@135lp/mm
Distortion	<0.051%(0.063%)
Detector type:	

7/4'	22.5×16.9	93.8×70.4mm
4/3'	18×13.5	75.0×56.3mm
1.1'	14.2×10.4	59.2×43.3mm
1'	12.8×9.6	53.3×40.0mm
2K Linear scan	2048×10μm	85.3mm
4K Linear scan	4096×7μm	119.5mm

XF-PTLAAABB-C/F/P/M-(L90E)

<p>The fourth generation lens of Canrill</p> <p>Object FOV</p> <p>Image FOV</p>	<p>The camera mount (M & P mount need specify BFL)</p> <p>90° Steering option</p>
--	---

Undefined tolerance (mm)	degree	File Name		
X. X	±0.2	±30min	XF-PTL13732-F-外形尺寸-EN	
X. XX	±0.02	Drawing Name		
X. XXX	±0.005	Drawing Size: A3		
	Sign	Data/Ver.	Material	Ratio
Design				1:5
Modify1			Qty	
Modify2			Total:	
			Page:	

All design and drawings are intellectual property of Canrill Optics, can not be copied without Canrill's authorization.